

- | | |
|--|---|
| 1. Unique identification code of the product-type: | Soft 78, Modern 78, Pure 78 – commercial version Classic, Quadrat FB, Integral window |
| 2. Intended use/es: | Wooden windows and balcony doors in aluminium cladding designed for use in residential and public utility buildings. |
| 3. Manufacturer: | FAKRO PP Sp. z o.o.
ul. Węgierska 144a,
33-300 Nowy Sącz, Poland
fakro@fakro.pl |
| 4. Authorised representative: | ./. |
| 5. System/s of AVCP: | 3 |
| 6. Harmonised standard:
Notified body/ies: | EN 14351-1:2006+A2:2016
ift Rosenheim (0757), Laboratorium Techniki Budowlanej (1827) |
| 7. Declared performance/s: | |

Essential characteristics		Performance	Harmonised technical specification
		Soft 78, Modern 78, Pure 78	
Glass unit		71U (4-12-4-12-4)	EN 14351-1:2006+A2:2016
7.1	Resistance to wind load	Class C3/B3 (1)	
7.2	Watertightness	Class 8A	
7.3	Dangerous substances	npd (2)	
7.4	Load-bearing capacity of safety device	Threshold value (350 N)	
7.5	Acoustic performance	npd	
7.6	Thermal transmittance Uw	1.1 [W/m ² K] (3), (4)	
7.7	Radiation properties: - Light transmittance τ _v - Solar factor g	0.74 0.53	
7.8	Air permeability	Class 4	

(1) for the windows with the width of >2.20 m and height of >2.20 m: npd (2) npd – no performance determined, (3) reference dimension (1.23 x 1.48 m) – calculation according to standard PN-EN ISO 10077-1, p. 6, (4) for windows with cross bars the thermal transmittance (Uw) should be increased by 0,2 W/m²K according to EN 14351-1:2006+A2:2016 Annex J.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 03/07/2019

